



# PLASTEC VENTILATION, INC.

www.plastecvent.net Phone: 941-751-7596 Fax: 941-751-7598

## Submittal Data and Specifications

### Transitions, Rigid (TR)

**Material of Construction and Temperature Limitations:**

Shall be made of UV treated polypropylene. Recommended up to 140° F.

**Application:**

Provides transition to Plastec Blowers or JET Series Fans to standard round PVC schedule 40 duct, weather cap or weather cap/stack.

**Manufacturer:**

Shall be manufactured under the authority of Plastec Ventilation, Inc.

**Shall have the following Features and Benefits:**

- Color coded to match Plastec Blower or JET Series Fan
- UV treated
- Corrosion resistant

**Warranty:**

This equipment is warranted to be free from defects in material and workmanship for two years from date of original shipment. For the complete warranty agreement, see I, O & M on [www.plastecvent.net](http://www.plastecvent.net).



DIMENSIONAL DATA (inches)				
Blower	Model	Inside Diameter	Outside Diameter	Length
Plastec 20 / Jet 20	TR20 (yellow)	6.4	6.6	4.1
Plastec 25 / Jet 25	TR25 (red)	8.0 / 8.5	8.2 / 8.6	4.4
Plastec 30 / Jet 30	TR30 (blue)	9.8 / 10.0	10.5 / 10.7	4.4

PROJECT			ARCHITECT	
CONTRACTOR	DATE	SUBMITTED BY		ENGINEER
SPECIFICATION				
RELATED FAN POSITION	MODEL #	QTY	NOTES	