PLASTEC VENTILATION, INC.

www.plastecvent.net Phone: 941-751-7596 Fax: 941-751-7598

Submittal Data and Specifications

Roof Unit Kits

Material of Construction and Temperature Limitations:

All parts shall be made of polypropylene. Mounting hardware will be made of stainless steel. Recommended up to 140° F.

Application:

Designed for utility blower roof curb mounting for Plastec utility blower models P15 through P30. Side wall mounting is optional on most models. Not available for models with Explosion-Proof Motors.

Manufacturer:

Shall be manufactured under the authority of Plastec Ventilation, Inc.

Shall have the following Features and Benefits:

- Injection moulding process to provide uniform thickness and strength.
- Corrosion resistant
- Horizontal discharge with roof curb mounting or side wall mount
- Roof curb or wall mounting for RU15 through RU30
- Attractive design
- Optional disconnect switch
- Easy access for any maintenance when required
- Includes roof curb cap base, weather cover for motor and exhaust guard
- UV treated
- Discharge to 8 different positions in 45° increments

Warranty:

This equipment is warranted to be free from defects in material and workmanship for two years from date of original shipment. For the complete warranty agreement, see I, O & M on **www.plastecvent.net**.

PROJECT			ARCHITECT
CONTRACTOR	DATE	SUBMITTED BY	ENGINEER

SPECIFICATION

RELATED FAN POSITION	MODEL #	QTY	NOTES