



PLASTEC VENTILATION, INC.

www.plastecvent.net Phone: 941-751-7596 Fax: 941-751-7598

Submittal Data and Specifications

Transitions, Rigid (TR)

Material of Construction and Temperature Limitations:

Shall be made of UV treated polypropylene. Recommended up to 140° F.

Application:

Provides transition to Plastec Blowers or JET Series Fans to standard round PVC schedule 40 duct, weather cap or weather cap/stack.

Manufacturer:

Shall be manufactured under the authority of Plastec Ventilation, Inc.

Shall have the following Features and Benefits:

- Color coded to match Plastec Blower or JET Series Fan
- UV treated
- Corrosion resistant

Warranty:

This equipment is warranted to be free from defects in material and workmanship for two years from date of original shipment. For the complete warranty agreement, see I, O & M on www.plastecvent.net.



DIMENSIONAL DATA (inches)				
Blower	Model	Inside Diameter	Outside Diameter	Length
Plastec 15	TR15 (gray)	4.4 / 5.0	4.6 / 5.2	3.7
Plastec 20 / Jet 20	TR20 (yellow)	6.4	6.6	4.1
Plastec 25 / Jet 25	TR25 (red)	8.0 / 8.5	8.2 / 8.6	4.4
Plastec 30 / Jet 30	TR30 (blue)	9.8 / 10.0	10.5 / 10.7	4.4

PROJECT			ARCHITECT	
CONTRACTOR	DATE	SUBMITTED BY		ENGINEER
SPECIFICATION				
RELATED FAN POSITION	MODEL #	QTY	NOTES	