



PLASTEC VENTILATION, INC.

www.plastecvent.net Phone: 941-751-7596 Fax: 941-751-7598

Submittal Data and Specifications

Vibration Isolators – VI4 and VI4XL

Material of Construction and Temperature Limitations:

Shall be made of rubber. Mounting hardware made of stainless steel and clear zinc plated threads. Temperature recommended up to 140° F.

Application:

Effective for vibration isolation in mounting fans.

Manufacturer:

Shall be manufactured under the authority of Plastec Ventilation, Inc.

Shall have the following Features and Benefits:

VI4


- Resistant to abrasion
- Maximum load downward compression of 45 lbs each (set of 4)
- Maximum load sideways shear of 8 lbs each (set of 4)
- 5/16" zinc plated threads

VI4XL

- Resistant to abrasion
- Maximum load downward compression of 370 lbs (set of 4)
- Maximum load sideways shear of 90 lbs each (set of 4) 360 lbs maximum
- 5/16-18" zinc plated threads, MID x 1.50

Warranty:

This equipment is warranted to be free from defects in material and workmanship for two years from date of original shipment. For the complete warranty agreement, see I, O & M on www.plastecvent.net.



PROJECT			ARCHITECT	
CONTRACTOR	DATE	SUBMITTED BY		ENGINEER
SPECIFICATION				
RELATED FAN POSITION	MODEL #	QTY	NOTES	